



DM5.5140 230V | 400V

ELEVADOR 4 COLUMNAS ELECTROHIDRÁULICO

- Electrohidráulico
- Equipado para alineación
- Placas traseras pivotantes
- Placas ajustables para platos de alineación
- Electroválvula de bajada
- Sistema de bloqueo electro-neumático
- Micros de seguridad de cables
- Micros de final de carrera

4 POST LIFT ELECTRO-HYDRAULIC

- Electro-hydraulic
- Equipped to handle alignment
- Shiding Plates
- Adjustable plates for geometry trays
- Electro magnetic lowering valve
- Pneumatic locking system
- Steel rope security switch
- Top himit switch

PONT ÉLEVATEUR À 4 COLONNES ÉLECTROHYDRAULIQUE

- Électrohydraulique
- Équipé pour gérer la géométrie
- Plaques arrière pivotantes
- Plaques réglables pour plateaux de géométrie
- Électrovanne de descente
- Système de verrouillage électro-pneumatique
- Micros contact de sécurité pour câbles
- Interrupteurs de fin de course


5000 KG



5000 KG



≤ 120 s



1900 mm



2.2 KW



2369 mm



**400V/3ph/50Hz
230V/1ph/50Hz**



3204 mm



4-6 bar



1350 KG

